

WH95FC • 14" Marine Crescent Ice Maker • Marine Series





WHITE SOLID (FLANGE TO CABINET)

FEATURES & BENEFITS

PERFORMANCE

- Uses less than 3 gallons (11,4 litres) of water to produce up to 23 lb (10,4 kg) of ice per day
- Up to 12 lb (5,4 kg) in ice storage capacity
- Crescent ice cube dimensions: $^{1}/^{2}$ " W x $^{3}/^{4}$ " H x 2 $^{1}/^{2}$ " L (12,7 mm W x 19 mm H x 63,5 mm L)
- On/Off switch is conveniently located on the grille
- Available in 115 or 220-240 volts

INTERIOR/EXTERIOR

• No drain required

- Door swing is field reversible
- Standard travel package includes door latch, ensuring safe-at-sea storage
- Corrosion and UV resistant components provide product longevity in harsh environments

INTEGRATION

• Unit is designed to be built-in or can be freestanding

- Accepts a 1/4" (6,4 mm) custom insert panel
- ½" (12,7 mm) flange mounts flush to cabinet

MODEL DETAILS

Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
ULN-WH95FC-03A	115 / 60	Field Reversible (Flange to Cabinet)	White Solid	62 lb (28 kg)
ULN-WH95FC-20A	220-240 / 50	Field Reversible	White Solid	62 lb (28 kg)

ACCESSORIES


Model	Description	Finish	Shipping Weight
WATERHOOKUP	Braided water supply line kit	N/A	2 lb (0,9 kg)
U-POWERCORD-2056*	Power Cord, 220-240v Great Britain/Ireland	Black	1 lb (0,5 kg)
U-POWERCORD-2667*	Power Cord, 220-240v Continental Europe	Black	1 lb (0,5 kg)
U-POWERCORD-2256*	Power Cord, 220-240v Australia/New Zealand	Black	1 lb (0,5 kg)
U-POWERCORD-3071*	Power Cord, 220-240v China	Black	1 lb (0,5 kg)
U-POWERCORD-3111*	Power Cord, 220-240v India	Black	1 lb (0,5 kg)

^{*}Power cord type must be specified with each U-Line order; no additional cost for power cord.




Marine Series • 14" Marine Crescent Ice Maker • WH95FC

DIMENSIONS



CABINET CUT-OUT



INSTALLATION NOTES

No additional clearance around sides, top or rear of unit is needed for ventilation.

Do not obstruct front grille air flow.

SPECIFICATIONS

	T	
Model	WH95FC	
Amps: Running (115v)	1.2 amps	
Amps: Running (220-240v)	1.2 amps	
Amps: Max Start Up (115v)	18 amps	
Amps: Max Start Up (220-240v)	6 amps	
Control Type	On/Off Switch	
Defrost Type	Manual	
Dimensions: Product Depth	17" (432 mm)	
Dimensions: Product Height	25 ½16" (637 mm)	
Dimensions: Product Width	14" (356 mm)	
ENERGY STAR	N/A	
Panel Type	Insert	
Panel Thickness	¹ / ₄ " (6.3 mm)	
Panel Height	13 ¹⁵ / ₃₂ " (342 mm)	
Panel Width	12 ¹⁵ / ₁₆ " (329 mm)	
Ice Production Per Day	23 lb (10,4 kg)	
Ice Storage	12 lb (5,4 kg)	
Product Weight: Max	56 lb (25 kg)	
Refrigerant Type	R134A	
Sabbath (Star K Certified)	No	
Marine Capable	Yes	



UL listing only applies to 115 v models.

CE only applies to 220-240v models.

Please visit U-Line.com to view this model's User Guide. All specifications are subject to change without notice.